



ZT510™
Industrial Printer

ZT510 vs. 105SLPlus Comparison Guide

Building on the legacy of its industry-leading 105SLPlus predecessor, the ZT510 strikes the ideal balance between exceptional performance and budget-friendly value. It provides the outstanding durability and reliability you expect from a Zebra printer, plus next-generation printing capabilities, advanced management and monitoring, and future-ready adaptability to power through every challenge in the years to come. Below is an overview of the ZT510's advantages.

User-Friendly Design

- Customizable, backlit, multi-line display including an intuitive menu, easy-to-use keypad and password protection
- Fast processing for quick throughput of even complex formats and graphic-based labels
- Dynamic QR codes that link to error-specific help videos

Future-Ready Adaptability

- Flexible design that allows hardware updates in the field, including cutter and peeler
- Two open communication slots to easily add connectivity options, including 802.11a/c, Parallel, IPv6* and USB Host

Printer Integration and Management

- Cloud-accessible Link-OS® Printer Profile Manager Enterprise to manage routing, firmware and more, on-site or remotely
- Mobile Device Management connectors to integrate networked printers into AirWatch or SOTI Device Management systems
- Operational Visibility Services (OVS) & Asset Visibility Services (AVS) for real-time insight into printer status, utilization and functionality
- Near Field Communication (NFC), used with the Link-OS Print Touch app, that allows users to pair Android devices

Printer Comparison**



Features	ZT510™		105SLPlus™	
Maximum Print Speed (per second)	203 dpi	12"/305 mm	203 dpi	12"/305 mm
	300 dpi	10"/254 mm	300 dpi	10"/254 mm
Maximum Print Width	4.09"/104 mm		4.09"/104 mm	
Standard Connectivity	<ul style="list-style-type: none"> • Serial • USB • Gigabit Ethernet • Bluetooth® LE 		<ul style="list-style-type: none"> • Serial • USB • Ethernet • Parallel 	
Optional Connectivity	<ul style="list-style-type: none"> • Parallel • 802.11a/c with Bluetooth® 4.0 • IPv6 • USB Host 		<ul style="list-style-type: none"> • ZebraNet 802.11b/g Print Server 	
Standard RAM	512 MB		16 MB	
Standard Flash	2 GB		8 MB	
User Interface	<ul style="list-style-type: none"> • Backlit, monochrome graphical LCD 		<ul style="list-style-type: none"> • Backlit, monochrome graphical LCD 	
Link-OS™ Enabled	Yes		No	
User Setup and Maintenance	<ul style="list-style-type: none"> • Print Touch • Dynamic QR Codes 		None	



NA and Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
contact.apac@zebra.com

EMEA Headquarters
zebra.com/locations
mseurope@zebra.com

Latin America Headquarters
+1 847 955 2283
la.contactme@zebra.com