



# MEMOR™ 1 - THE NEW DATALOGIC **GENERAL PURPOSE FULL TOUCH DEVICE**

Memor 1 is your business companion for any data capture application, from assisted sales to the shop floor, or backend receiving to the warehouse.

#### **MULTIPLE DEVICES IN ONE**

The Memor 1 device comes with a powerful Qualcomm Snapdragon platform and features Android™ 8.1 (Oreo) with GMS. This device is available in two form factors: a hand held version resembling a rugged smartphone or a pistol-grip version with a comfortable trigger. The robust black enclosure allows this device to be used in most any application.

# **WIRELESS CHARGING DOCKS - SINGLE AND 3-SLOT**

The Memor 1 device is charged using state-of-the-art wireless charging technology that eliminates the need for cleaning contacts on the device and docks. It radically reduces support costs and increases its reliability.

The 3-slot dock along with multiple single dock options support both hand held and pistol-grip models providing maximum flexibility.

## **BOOST AND FAST CHARGING**

The Memor 1 device requires less than 2 hours to fully charge the battery and the Boost Recharge allows use within minutes of charging. Six charging profiles are available to let the user decide which profile better suits their

# **VOICE COMMUNICATOR**

The Memor 1 device can also be used as a phone or PTT device using the Voice over Internet Protocol (VoIP), leveraging your Wi-Fi network for communications.

NOTE: The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.





















# **FEATURES**

- Multi-purpose device: hand held or pistol-grip
- Android 8.1 (Oreo) with Google Mobile Services
- Wireless charging eliminates all contacts on the device and dock
- Supports both Boost and Fast charging modes
- VoIP or PTT phone capabilities over Wi-Fi
- Presentation mode allows hands-free scanning
- Datalogic's SoftSpot™ technology for innovative triggering through the touch display
- 3-Axis Accelerometer auto-rotates the screen orientation
- 4.3 inch capacitive multi-touch FWVGA display with Gorilla® Glass 3
- Vibration alert for notifications
- Advanced 2D imaging technology with image capture
- Datalogic's patented 'Green Spot' technology for visual good-read feedback
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

# INDUSTRY-APPLICATIONS

- Retail:
  - Inventory
  - Access Control
  - Gift Registry
  - Shop Floor Applications
- Assisted Sales
- Manufacturing:
- Quality Control
- Inventory
- Logistics:
  - Inventory
  - Picking/Packing
  - Shipping/Receiving
  - Track & Trace



# **ODATALOGIC**

# TECHNICAL SPECIFICATIONS

#### WIRELESS COMMUNICATIONS

PERSONAL AREA NETWORK (WPAN)

LOCAL AREA NETWORK (WLAN) IEEE 802.11 a/b/g/n;

Wi-Fi Security Standards: WEP, WPA/WPA2 PSK, 802.1x EAP Methods: PEAP/MSCHAPV2, PEAP/GTC, TLS, TTLS/PAP, TTLS/MSCHAP, TTLS/

MSCHAPV2, TTLS/GTC, PWD

Bluetooth® wireless technology v4.0 - Dual Mode, supporting Classic Bluetooth and BLE NFC communication between device and dock

#### **DECODING CAPABILITY**

NFC COMMUNICATION

1D / LINEAR CODES

Auto discriminates all standard 1D codes including GS1 DataBar™linear codes.

2D CODES

Aztec Code, Data Matrix, MaxiCode, PDF417, Micro QR Code, QR Code

POSTAL CODES Australian Post, Japanese Post, KIX Code, Royal Mail, USPS Intelligent Mail, USPS PLANET, USPS

DIGITAL WATERMARKS Supports Digimarc® Barcode (optional)

**ELECTRICAL** 

BATTERY Replaceable battery pack with rechargeable
Li-lon batteries; 3.7 V; 3,000 mAh (12 Watt-hours)
WIRELESS CHARGING Two charging options: Fast charging or Standard
charging

#### **ENVIRONMENTAL**

DROP RESISTANCE

Withstands repeated drops from 1.2 m / 4.0 ft
onto plywood over concrete and 1.5 m / 5.0 ft
onto plywood over concrete with the rubber boot
accessory

TEMPERATURE Operating: -10 to 50 °C / 14 to 122 °F

**INTERFACES** 

INTERFACES USB 2.0 Client (with standard Micro-USB connector)

SDXC card slot (not user accessible)

SENSORS

ACCELEROMETER 3-Axis accelerometer to detect orientation
GYROSCOPE Senses angular velocity
VIBRATION Software programmable
MAGNETOMETER Senses angular velocity

#### PHYSICAL CHARACTERISTICS

DISPLAY 4.3 inch full touch TFT-LCD color display; FWVGA: 854 x 480 pixels; 16M colors, LED

backlight

TOUCH SCREEN Capacitive, multi-touch, Gorilla® Glass 3
PHYSICAL KEYS Handheld: Home/scan fully programmable key,
Pistol-Grip: Home/scan fully programmable key,

Scan Trigger key

LED/LIGHTING Software programmable, lights at the bottom of

the battery cover

DIMENSIONS Handheld: 14.5 x 7.7 x 3.4 cm / 5.7 x 3.0 x 1.3 in Pistol-Grip: 14.5 x 7.7 x 11.6 cm / 5.7 x 3.0 x 4.5 in

Handheld: 275.0 g / 9.7 oz Pistol-Grip: 305.0 g / 10.7 oz

#### **READING PERFORMANCE**

WEIGHT (WITH BATTERY)

DEPTH OF FIELD 4.3 to 35.0 cm / 1.7 to 13.8 in, depending on bar code density

MINIMUM RESOLUTION
Linear codes at 4 mils; 2D codes at 5 mils
Loudspeaker (Polyphonic); Datalogic's patented
'Green Spot' technology for visual good-read

feedback

#### **SAFETY & REGULATORY**

AGENCY APPROVALS

The product meets necessary safety and regulatory approvals for its intended use.

ENVIRONMENTAL COMPLIANCE

Complies to EU ROHS

#### **SOFTWARE**

APPLICATIONS

Datalogic's SoftSpot technology for configurable soft triggers; Supports Datalogic's Queue

Busting app; Pre-licensed device and browser

lockdown powered by 42Gears;
Enterprise class PTT offered by Zello
PROVISIONING Android Zero Touch enrollment
CONFIGURATION AND MAINTENANCE Datalogic DXU for device configuration and

firmware upgrade from PC
DEVELOPMENT Java and Xamarin SDK available
MDM SOTI MobiControl, VMWare AirWatch, Wavelink

Avalanche, 42Gears SureMDM
TERMINAL EMULATION StayLinked SmartTE, Wavelink Velocity

#### SYSTEM

MEMORY System RAM: 2 GB;

System Flash: 16 GB Flash Disk SD Card: Factory installed option U Qualcomm SnapDragon Quadcore 1 GHz

OPERATING SYSTEM Android 8.1 (Oreo) with GMS

#### WARRANTY

WARRANTY 1-Year Factory Warranty



Integer Solutions GmbH Industriestraße 4 D-61200 Wölfersheim Tel. +49 (0)6036-90557-0 office@integer-solutions.com

## Docks and Holders



■ 94ACC0206 3-Slot Dock



 94ACC0207 Single Slot Dock Locking



 94ACC0208 Single Slot Dock Charge only

# Cases/Holsters



Rubber Boot



• 94ACC0210 Pistol Grip Rubber Boot



• 91ACC0080 Belt Holster